
1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CARBON DIOXIDE CYLINDER, GAS AND LIQUID WITHDRAWAL
Synonym(s) 030 - SDS NUMBER • 206, 207, 261 • CARBON DIOXIDE, COMPRESSED • FOGG GAS • PRODUCT CODES: 080, 081, 082, 083, 084, 086, 131, 176, 200 • REFRIGERANT 744

1.2 Uses and uses advised against

Use(s) DISPENSING GAS • INERT GAS • SHIELDING GAS

1.3 Details of the supplier of the product

Supplier name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Website <http://www.boc.com.au>

1.4 Emergency telephone number(s)

Emergency 1800 653 572 (24/7) (Australia only)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS (GHS ONLY) ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Gases Under Pressure: Liquefied gas

2.2 Label elements

Signal word WARNING

Pictogram(s)



Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

None allocated.

Response statement(s)

None allocated.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.

2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

| Ingredient | CAS Number | EC Number | Content (v/v) |
|----------------|------------|-----------|---------------|
| CARBON DIOXIDE | 124-38-9 | 204-696-9 | >99.9% |

4. FIRST AID MEASURES

4.1 Description of first aid measures

| | |
|-----------------------------|---|
| Eye | Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate for 15 minutes. Seek medical attention. |
| Inhalation | If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor. |
| Skin | Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15 minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for 15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention. |
| Ingestion | Due to product form and application, ingestion is considered unlikely. |
| First aid facilities | None allocated. |

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Direct contact with the liquefied material or escaping compressed gas may cause frostbite injury. Low concentrations of CO₂ cause increased respiration and headache.

4.3 Immediate medical attention and special treatment needed

Treat for asphyxia and cold burns.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable.

5.3 Advice for firefighters

Temperatures in a fire may cause liquid vessels and related equipment to rupture. Storage vessels may contain fine particle insulation materials or foam products which may be hazardous or release hazardous decomposition products in a fire. Cool vessels exposed to fire by applying water from a protected location. Do not approach vessels suspected of being hot. Evacuate area if unable to keep vessels cool.

5.4 Hazchem code

2T
 2 Fine Water Spray.
 T Wear full fire kit and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS. Ventilate area where possible and eliminate ignition sources.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Stop the flow of material, if this is without risk. If the leak is irreparable, move the cylinder to a safe and well ventilated area, and allow to discharge. Keep area evacuated and free from ignition sources until any leaked or spilled liquid has evaporated.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Refer to vessel operating instructions. Do not store near incompatible substances, heat or ignition sources and foodstuffs. Portable liquid containers should be stored: upright, prevented from falling, in a secure area; below 45°C, in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

| Ingredient | Reference | TWA | | STEL | |
|------------------------------|-----------|-------|-------------------|-------|-------------------|
| | | ppm | mg/m ³ | ppm | mg/m ³ |
| Carbon dioxide | SWA (AUS) | 5000 | 9000 | 30000 | 54000 |
| Carbon dioxide in coal mines | SWA (AUS) | 12500 | 22500 | 30000 | 54000 |

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

- Eye / Face** Wear safety glasses.
- Hands** Wear leather or insulated gloves.
- Body** Wear coveralls.
- Respiratory** Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | |
|------------------------------|--|
| Appearance | COLOURLESS GAS |
| Odour | ODOURLESS |
| Flammability | NON FLAMMABLE |
| Flash point | NOT RELEVANT |
| Boiling point | NOT AVAILABLE |
| Melting point | NOT AVAILABLE |
| Evaporation rate | NOT APPLICABLE |
| pH | NOT APPLICABLE |
| Vapour density | NOT AVAILABLE |
| Specific gravity | NOT APPLICABLE |
| Solubility (water) | 0.759 cm ³ /cm ³ |
| Vapour pressure | 6300 kPa @ 25°C (Approximately) |
| Upper explosion limit | NOT RELEVANT |
| Lower explosion limit | NOT RELEVANT |
| Partition coefficient | NOT AVAILABLE |

9.1 Information on basic physical and chemical properties

| | |
|----------------------------------|---------------|
| Autoignition temperature | NOT AVAILABLE |
| Decomposition temperature | NOT AVAILABLE |
| Viscosity | NOT AVAILABLE |
| Explosive properties | NOT AVAILABLE |
| Oxidising properties | NOT AVAILABLE |
| Odour threshold | NOT AVAILABLE |

9.2 Other information

| | |
|--------------------------------------|---------------------------------|
| % Volatiles | 100 % |
| Critical pressure | 7,380 kPa (Approximately) |
| Critical temperature | 31°C (Approximately) |
| Cylinder pressure (when full) | 6300 kPa @ 25°C (Approximately) |
| Density | 1.53 (Air = 1) |
| Sublimation temperature | -78°C (Approximately) |

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid contact with incompatible substances.

10.5 Incompatible materials

Moist carbon dioxide is corrosive, hence acid resistant materials are required (e.g. stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide (i.e. embrittlement, leaching of plasticisers, etc).

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Low concentrations of carbon dioxide cause increased respiration and headache.

Information available for the ingredient(s):

| Ingredient | Oral Toxicity (LD50) | Dermal Toxicity (LD50) | Inhalation Toxicity (LC50) |
|----------------|----------------------|------------------------|----------------------------|
| CARBON DIOXIDE | -- | -- | 470000 ppm/30M (rat) |

| | |
|---------------------------------|--|
| Skin | Not classified as a skin irritant. Contact with dry ice powder may cause frostbite injury or cold burns. |
| Eye | Not classified as an eye irritant. Contact with dry ice powder may cause frostbite injury or cold burns. |
| Sensitisation | Not classified as causing skin or respiratory sensitisation. |
| Mutagenicity | Not classified as a mutagen. |
| Carcinogenicity | Not classified as a carcinogen. |
| Reproductive | Not classified as a reproductive toxin. |
| STOT – single exposure | Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness, drowsiness, weakness, fatigue, breathing difficulties and unconsciousness. |
| STOT - repeated exposure | Not classified as causing organ damage from repeated exposure. |
| Aspiration | Not classified as causing aspiration. |

12. ECOLOGICAL INFORMATION

PRODUCT NAME CARBON DIOXIDE CYLINDER, GAS AND LIQUID WITHDRAWAL

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Ensure all liquid and gas supply valves are shut. Notify the manufacturer that you will be returning the portable liquid container. Residual product will be disposed of under the manufacturer's supervision.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



| | LAND TRANSPORT (ADG) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|-----------------------------|----------------------|----------------------------|-----------------------------|
| 14.1 UN Number | 1013 | 1013 | 1013 |
| 14.2 Proper Shipping Name | CARBON DIOXIDE | CARBON DIOXIDE | CARBON DIOXIDE |
| 14.3 Transport hazard class | 2.2 | 2.2 | 2.2 |
| 14.4 Packing Group | None allocated. | None allocated. | None allocated. |

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code 2T
GTEPG 2C1
EMS F-C, S-V

Other information Transport on open top vehicles in accordance with Australian Code for the Transport of Dangerous Goods. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

| | |
|-----------------------------|---|
| Hazard codes | None allocated. |
| Risk phrases | None allocated. |
| Safety phrases | None allocated. |
| Inventory listing(s) | AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt. |

16. OTHER INFORMATION

Additional information The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas withdrawal: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment. Liquid withdrawal: may be used as liquid or vapourised for pressure regulated gas distribution.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

| | | |
|----------------------|-------------------|---|
| Abbreviations | ACGIH | American Conference of Governmental Industrial Hygienists |
| | CAS # | Chemical Abstract Service number - used to uniquely identify chemical compounds |
| | CNS | Central Nervous System |
| | EC No. | EC No - European Community Number |
| | EMS | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) |
| | GHS | Globally Harmonized System |
| | GTEPG | Group Text Emergency Procedure Guide |
| | IARC | International Agency for Research on Cancer |
| | LC50 | Lethal Concentration, 50% / Median Lethal Concentration |
| | LD50 | Lethal Dose, 50% / Median Lethal Dose |
| | mg/m ³ | Milligrams per Cubic Metre |
| | OEL | Occupational Exposure Limit |
| | pH | relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). |
| | ppm | Parts Per Million |
| | STEL | Short-Term Exposure Limit |
| | STOT-RE | Specific target organ toxicity (repeated exposure) |
| | STOT-SE | Specific target organ toxicity (single exposure) |
| | SUSMP | Standard for the Uniform Scheduling of Medicines and Poisons |
| | SWA | Safe Work Australia |
| | TLV | Threshold Limit Value |
| | TWA | Time Weighted Average |

PRODUCT NAME CARBON DIOXIDE CYLINDER, GAS AND LIQUID WITHDRAWAL

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au.

[End of SDS]